

**SUPPORT APPARATUS WITH INTERCHANGEABLE INSERTS****FIELD OF THE INVENTION**

10       The present invention relates generally to therapeutic support braces and more particularly relates to an improved construction and arrangement for a brace with interchangeable inserts.

**BACKGROUND OF THE INVENTION**

15       Prior art devices of this type have relied on a variety of different designs and constructions to support the wrist during repetitive actions such as typing, cumulative trauma, or sport related repetitive  
20       motions which impart injury, etc. Accordingly, a number of prior art devices have been developed that are made of reinforced synthetic fabric material, such as nylon that use multiple securing straps that are typically secured to oppositely disposed portions of the braces by  
25       VELCRO type hook and loop fasteners.

      What is needed is a support apparatus that is capable of being used with an infinite number of interchangeable inserts for the application of heat, cold, or massage inside the support apparatus.

30

**SUMMARY OF THE INVENTION**

      The present invention meets the above described need by providing a support apparatus with interchangeable inserts that includes a base member with  
35       an elongate body. The elongate body includes a hook and loop fastening surface for removably attaching interchangeable inserts. The base member attaches to the body of the user in end-to-end fashion. Securing straps and an anchoring ring provide additional support  
40       to keep the base member in position. The inserts are removably attached to the base member such that they are disposed against the body of the user when the apparatus

2025-01-07 10:06:47

5 is in use. The inserts may have different textures for tactile sensations and may be provided with cavities containing fluid or gel for transmitting heat or cold to the body of the user.

10 BRIEF DESCRIPTION OF THE DRAWINGS

The invention is illustrated in the drawings in which like reference characters designate the same or similar parts throughout the figures of which:

15 Figure 1 is a perspective view of the base member of the present invention;

Figure 2 is a perspective view of the base member of Fig. 1 in a curved position for wrapping around the arm of the user;

20 Figure 3 is a perspective view of the base member of Fig. 1 in as it would appear after being wrapped around the user's arm and secured;

Figure 4 is a perspective view of an alternate embodiment of the base member of Fig. 1;

25 Figure 5 is a perspective view of the base member of Fig. 4 in a curved position for wrapping around the arm of the user

Fig. 6 is a perspective view of an insert for the base member;

30 Fig. 7 is a perspective view of the opposite side of the base member shown in Fig. 6;

Fig. 8 is a perspective view of an alternate embodiment of the insert;

35 Fig. 9 is a perspective view of another alternate embodiment of the insert;

Fig. 10 is a perspective view of the opposite side of the insert shown in Fig. 9;

Fig. 11 is a perspective view of another alternate embodiment of the insert;

5        Fig. 12 is a perspective view of another alternate embodiment of the insert;

      Fig. 13 is a perspective view of the opposite side of the insert shown in Fig. 12;

10       Fig. 14 is a perspective view of another alternate embodiment of the insert;

      Fig. 15 is a perspective view of a cover for the insert shown in Fig. 14; and,

      Fig. 16 is a top plan view of an alternate embodiment of the present invention.

15

#### DETAILED DESCRIPTION

20       In Fig. 1, a base member 20 includes an elongate body 23 having a first surface 26. The body 23 extends in the longitudinal direction from a first end 27 to a second end 28. The body 23 is also bordered by a pair of opposed sides 30 and 31. The elongate body 23 may be constructed of any elastic material suitable for use as a support member. The material is stretchable with elastic characteristics and may also be water resistant.

25       One material that is suitable for this purpose is sold under the brand name LYCRA. Other materials having similar characteristics would also be suitable for the material of the elongate body 23.

30       As shown in Fig. 2, the first surface 26 is located on the inside when the base member 20 is wrapped around the body of the user such as the wrist or forearm. Returning to Fig. 1, a hook and loop fastening surface 29 is disposed on the first surface 26 of body 23. As known to those of ordinary skill in the art, hook and

35       loop fastening systems include a coacting hook portion on a first member and a loop portion on a second member. The hook and loop portions are capable of being removably attached to one another and provide a convenient fastening system that may be used in place of

20250715 15:03:10

5 buttons or the like. A well known hook and loop  
fastening system is sold under the brand name VELCRO.  
Surface 29 may comprise either the hook or the loop  
portion of the hook and loop fastening system as will be  
described in greater detail below.

10 The body 23 has a major longitudinal dimension that  
varies depending on the intended use for the base member  
20. The width 32 of the body 23 also varies depending on  
the intended use. For example, the body 23 shown in  
Figs. 1-3 is intended for use as a wrist support,  
15 whereas the body 103 shown in Figs. 4 and 5 is intended  
for use as a wrist and forearm support. Accordingly,  
the body 103 may be slightly longer and may be wider to  
accommodate the forearm of the user. Similar support  
members with varying dimensions may also be used for the  
20 hand, elbow, knee or foot. It is to be understood that  
the present invention may be applied to any support  
apparatus with interchangeable inserts and capable of  
being attached to the body of a user. The wrist and  
forearm mounted device shown in the illustrations is one  
25 example of the invention and the invention is not  
intended to be limited to a support apparatus mounted to  
the wrist or wrist and forearm.

In Fig. 2 a pair of straps 35 extend from a second  
surface 38 of the body 23. Although a pair of straps  
30 are shown, the number of straps is not critical and a  
single, wider strap or additional straps (Figs. 4 and  
5) could also be used. The second surface 38 is located  
on a side of the body 23 that is opposite from the first  
surface 26. When the base member 20 is wrapped around  
35 the wrist of the user, the second surface 38 faces  
outward. The straps 35 may be attached to the second  
surface 38 at a point between the ends 27 and 28 of body  
23.

5       A pair of leverage rings 41 are attached to the  
second surface 38. The straps 35 have a first hook or  
loop portion 44 of a hook and loop fastening system  
disposed at the ends thereof and a second hook or loop  
portion 47 of a hook and loop fastening system disposed  
10 between the ends of the straps 35.

      The second surface 38 also has a hook or loop  
portion 50 disposed near an end of the body 23. As  
shown, the opposing ends 27 and 28 are attached to one  
another in end-to-end fashion by means of hook or loop  
15 portion 50 and the hook and loop fastening surface 29  
disposed on the first surface 26.

      In Fig. 3, the straps 35 are shown as they attach  
around the body 23 to further secure base member 20 in  
position around the wrist of the user. The straps 35  
20 are wrapped around the second surface 38 of body 23 and  
then inserted into the leverage rings 41. The straps 35  
are folded about the leverage rings 41 and then the ends  
of the straps 35 extend in the opposite direction and  
the hook or loop portion 44 on the end of the straps 35  
25 is attached to the hook or loop portion 47 disposed  
between the opposite ends of the straps 35.

      Turning to Figs. 4 and 5, in an alternate  
embodiment base member 100 has a body 103 that is  
suitable for use to support both the wrist and forearm.  
30 The body 103 has two opposed ends 104 and 105 and a  
first surface 106 with a pair of hook and loop fastening  
surfaces 109 and 112 disposed along the length of the  
body 103. As shown in Fig. 5, a second surface 115 of  
body 103 has a pair of hook and loop fastening surfaces  
35 104 disposed at or near the end 105 of the body 103.  
The body 103 is attached around the wrist and forearm in  
end-to-end fashion and then the straps 118 are attached  
around the body 103 as described above in connection  
with Figs. 1-3.

Turning to Figs. 6-7, the hook and loop fastening surfaces 29, 102, and 112 are capable of receiving multiple inserts either individually or in combination as described below. Insert 200 has a first surface 201 containing a plurality of projections 203 that provide a tactile surface with massage-like qualities. A second surface 205 opposite the first surface has a hook and loop fastening surface 208 disposed thereon. The hook and loop fastening surface 208 is capable of removably attaching to surfaces 29, 109, 112 such that the insert 200 is held in position against the body of the user by the base member 20 or 100.

Turning to Fig. 8, in an alternate embodiment an insert 300 is formed out of a sheet of absorbent cotton or like material. The insert 300 provides a surface for absorbing the perspiration of the user.

In Figs. 9 and 10, an oval-shaped member 350 having a cavity is shown. Other shapes for the hollow member would also be suitable. A gel is disposed inside the cavity. A hook and loop fastening surface 353 is disposed on a bottom surface 356.

In Fig. 11, insert 400 is constructed of a perforated foam for ventilation. In Figs. 12 and 13, an insert 450 has a magnet enmeshed in a member. A hook and loop fastening surface 453 is disposed on a bottom surface 456.

In Fig. 14, insert 500 comprises a gel insert that may be heated or cooled. In Fig. 15, a slip cover 550 is shown. The slip cover 550 provides for storing and protecting the insert between uses.

As described above, an infinite number of interchangeable inserts can be formed out of different materials for different purposes. The materials may have different textures for different tactile sensations. The materials may have internal cavities

5 for storing different liquids that may be used for  
transmitting heat or cold to the body. The liquids may  
also be used to provide a different type of support than  
the solid surfaces.

Turning to Fig. 16, an alternate embodiment of the  
10 present invention is shown. A base member 600 is  
attached to the hand 601 of the user by straps 603 that  
may attach around the palm and around the fingers. The  
base member 600 includes a hook and loop fastening  
15 surface 606 disposed on the side opposite from first  
surface 609. A plurality of inserts 612 having  
different tactile surfaces or liquid or gel filled  
cavities, which can be similar to the inserts described  
above in connection with Figs. 6-14, may be used  
interchangeably with base member 600. As described  
20 above, the inserts 612 are attached to the base member  
600 by means of coacting hook and loop fastening  
surfaces.

While the invention has been described in  
connection with certain embodiments, it is not intended  
25 to limit the scope of the invention to the particular  
forms set forth, but, on the contrary, it is intended to  
cover such alternatives, modifications, and equivalents  
as may be included within the spirit and scope of the  
invention as defined by the appended claims.

30